www.clovercooler.com

BL25

HOT/COLD **BOTTOM LOAD**















FREE

MERCURY -FREE





ENERGY

SAVING



Bottom Load Water Cooler BL25 Specifications

MODEL	BL25
STAINLESS STEEL COLD TANK CAPACITY	0.63 GALLONS
STAINLESS STEEL HOT TANK CAPACITY	0.42 GALLONS
UV LED LIGHT	3 YEARS (3 HOURS PER DAY)/3,000 HOURS
LOW NOISE PUMP	3 YEARS / 10,000 CYCLES
CERTIFICATES	UL, ENERGY STAR
DIMENSIONS	12. 2 ″ W x 13.58 D x 43.3″ H
COLOR	BLACK

Specifications are subject to change without notice.



CABINET

Top and front panels are molded of ABS plastic and side panels are made of electric zinccoated steel with high polymer polyester

FAUCETS

Durable polypropylene. Self closing type. Easy to operate. Safety hot water faucet.

DRIP TRAY

Concealed, lift-out design, high impact, durable ABS plastic. Removable, anti-splash grid diverts drip water.

REFRIGERATION UNIT

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector.

No lubricant is needed. Refrigerant is controlled by accurately calibrated capillary tube.

HOT WATER THERMOSTAT

Water Temperature is controlled to 185°F by an automatic thermostat.

ON/OFF switch is easily accessible on the rear control panel.

HOT WATER TANK

Hygienic stainless steel tank with a highly efficient internal heating element.

COLD WATER THERMOSTAT

Easily control the temperature from 39.2°F - 50°F by using the adjustable, easily located thermostat on the back panel

COLD WATER TANK

High capacity, hygienic stainless steel tank. Large enough volume for most RO filtration systems.

LG BRAND COMPRESSOR

All Clover coolers come standard with a LG brand compressor.

Each cooler has LG's highest quality compressor with the low cycle rates. (manufactured in South Korea not China).













