



Introducing the Commercial Grade
Uniserve Brewer. Serviceable, Reliable,
K-Cup® Compatible.
Order today!

PERFORMANCE & DURABILITY

Compatible with ALL K-Cups®

The Uniserve Brewer has been purpose built to be compatible with all K-Cup coffee brands. Ensuring an outstanding cup of coffee.

Never Wait for Another Cup Again!

Under 45 second recovery time to optimal temperature. Keeps your cup full of your favorite K-Cup® beverage.

No Lukewarm Beverages Here!

Steaming hot beverages up to 198 degrees at the touch of a button.

Commercial Volume

Enjoy 10 - 8oz cups before easily refilling the removable water reservoir. Direct plumed-in capability available.

Every Cup. Every Time.

Superior made Japanese hot water pump built to last for years, keeping your commercial grade, serviceable brewer running consistently.

Energy Saving

Save energy utilizing the energy saving option, featured on the Uniserve Brewer.

COMMERCIAL GRADE ADVANTAGE

Better Than Your Average Brand K-Cup® Brewer

Higher heat and bar pressure extracts the most from your coffee, providing a superior taste and experience.

Office Volume Commercial Reservoir

With a large 65 oz external reservoir and a hot tank flow capacity of 4.3 gallons per hour, the whole office is never without their favorite K-Cup® beverage.

Quality Defined

South Korean manufactured brewer with Italian and Japanese components delivering the most reliable brewing system to the HOD and OCS market.

Compact Power

Compact design to fit anywhere, without compromising performance.

Uniserve Strong

Never cut the cord! Order the serviceable Uniserve Brewer with confidence. major components easily serviced.

UNISERVE™

COMMERCIAL GRADE BREWER



SINGLE SERVE COFFEE BREWER SPECIFICATIONS

MODEL	T1B
Hot Tank	1300W, 176 °F - 198 °F
Hot Tank Flow Capacity	4.3 gal/hr - 20 oz static capacity
Water Pump	12VDC
Air Pump	12VDC
Certification	UL, NSF
Net Size	7.5 in (w) x 12.6 in (d) x 11.8 in (h)
Shipping Size	8.6 in (w) x 13.7 in (d) x 13 in (h)
Net Weight	6.6 lbs
Shipping Weight	7.7 lbs
Container Loading (pallet packing)	90 units (1 pallet) / 1,980 units (40ft)
Life Cycle	15,000 cycles (6oz cup)

REPLACEABLE SERVICE PARTS

- Brewing Chamber
- Lever
- Drip Tray
- Reservoir Exterior
- Air Pump
- Thermostat
- Hot Tank Assembly
- Transformer
- Main PCB (Printed Computer Board)
- Display PCB (Printed Computer Board)

FEATURES

- K-cup® capsule compatible
- 3 BAR pressurized brewing chamber
- Commercial grade construction & contemporary styling
- Commercial grade components sourced from Italy, Japan & South Korea ensure long life under the heaviest of use
- Serviceable/Repairable (HOD/Warranty Repair)
- Large 65oz external reservoir
- Pour over or plumb-in capability with easy to install conversion kit (sold separately)
- UL listed for commercial use
- Eco mode: adjustable sleep mode puts the unit to 'sleep' after 1 hour or 3 hours of no use
- Auto off: after 40 minutes in eco mode, brewer will shut off
- Each brewing cycle concluded with 6 BAR air cycle which clears the brewing chamber of excess hot liquid
- Low water indication light
- Highly efficient heating element will prime the unit from the off position in just 60 seconds, allowing you to enjoy endless cups without any wait time